NSN 6625-00-668-7811

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-668-7811

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

1.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.312 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.312 inches

Overall Height:

1.810 inches

Overall Width:

1.810 inches

Scale Division Quantity:

10 single indicator single range

Mounting Stud Length:

0.375 inches

Environmental Protection:

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

Furnished Items And Quantity:

Mtg hdw 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.250 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

NSN 6625-00-668-7811

Ammeter - Page 2 of 2



Pointer Color: Black single indicator single range **Power Source:** External Mounting Facility Type And Quantity: 4 threaded stud Scale Graduation Type: Linear single indicator single range Measurement Range: +0.0/+1.0 milliamperes, dc single indicator single range **Mounting Stud Diameter:** 0.125 inches **Scale Selection Method:** Terminal **Features Provided:** Luminous scale marking and magnetic shield and zero adjuster **Movement Suspension Method:** Jewel pivot base **Circuit Attachment Method And Quantity:** 2 solder lug and 2 threaded stud **Special Features:** Ruggedized Material: Steel **Nuclear Hardness Critical Feature:** Nonhardened Style Designator: Rectangular flush mtg **Test Data Document:** 81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Fsc Application Data:** Test set, elect. Equip. Shelf Life: N/a Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0