# NSN 6625-00-668-8049

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-668-8049

# Circuit Current For Which Designed:

Dc

# **Dielectric Withstanding Voltage In Volts:**

3000.0

# **Overall Length:**

2.850 inches

# Mounting Hole Diameter:

0.150 inches

## Scale Division Quantity:

40 single indicator single range

# **Overall Diameter:**

3.510 inches

# **Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

# Mounting Bolt Circle Diameter:

3.160 inches

# **Furnished Items And Quantity:**

Nut 7; lockwasher 3; flat washer 4; seal 1

## Indicator Type:

Dial w/pointer

# Installation Design:

Panel

# Mounting Arrangement Style:

Three hole/stud bolt circle

## Sensitivity Rating:

150.0 millivolts

# **Dial Scale Marking Color:**

Black single indicator single range

#### Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

# Meter Depth Behind Mounting Flange:

1.660 inches

# Meter Body Diameter Behind Mounting Flange:

2.800 inches

## Movement Type:

Moving iron vane

# **Background Color:**

White single indicator single range

# **Pointer Color:**

Black single indicator single range

# Power Source:

External

# NSN 6625-00-668-8049

Voltmeter - Page 2 of 2



# Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

## Scale Graduation Type:

Linear single indicator single range

# Measurement Range:

+0.0 to 200.0 volts, dc single indicator single range

## **Scale Selection Method:**

Terminal

## **Features Provided:**

External shunting and zero adjuster

## **Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:** 

2 solder lug and 2 threaded stud

### **Special Features:**

Ruggedized

### **Special Markings:**

On back, sealed do not open

Material:

Steel

**Nuclear Hardness Critical Feature:** 

# Nonhardened

Surface Treatment:

Paint

## Style Designator:

Round flush mtg

# Test Data Document:

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

81349-mil-m-10304/11 government specification

### Fsc Application Data:

Test set, elect. Equip.

### Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

Fiig:

A310a0