NSN 6625-00-668-9186

Ammeter - Page 1 of 2

External



View Online at https://aerobasegroup.com/nsn/6625-00-668-9186

Circuit Current For Which Designed: Dc **Dielectric Withstanding Voltage In Volts:** 3000.0 **Overall Length:** 2.850 inches **Mounting Hole Diameter:** 0.150 inches Scale Division Quantity: 75 single indicator single range **Overall Diameter:** 3.510 inches **Environmental Protection:** Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight Mounting Bolt Circle Diameter: 3.160 inches **Furnished Items And Quantity:** Nut 7; lockwasher 5; seal 1 Indicator Type: Dial w/pointer Installation Design: Panel **Mounting Arrangement Style:** Three hole/stud bolt circle **Dial Scale Marking Color:** Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range **Unable To Decode:** Unable to decode or unable to decode Meter Depth Behind Mounting Flange: 1.660 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Movement Type: Moving iron vane **Background Color:** White single indicator single range **Pointer Color:** Black single indicator single range **Power Source:**

NSN 6625-00-668-9186

Ammeter - Page 2 of 2



Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+150.0 milliamperes, rf single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Luminous scale marking and magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Test Data Document:

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-10304/15 government specification

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A310a0