NSN 6625-00-668-9211

Voltmeter - Page 1 of 2

Dc

Overall Length: 1.438 inches

0.125 inches

Mounting Hole Diameter:

Scale Division Quantity:

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-668-9211

| 100 single indicator single range |
|--|
| Overall Diameter: |
| 2.695 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 1000.0 ohms per volt |
| Dial Scale Marking Color: |
| Yellow single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator all ranges |
| Unable To Decode: |
| Unable to decode or unable to decode |
| Meter Depth Behind Mounting Flange: |
| 1.063 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.150 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Measurement Range: |
| +0.0 to 500.0 volts, dc single indicator single range |
| Features Provided: |
| Electrostatic shield and magnetic shield and zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 solder lug |

NSN 6625-00-668-9211

Voltmeter - Page 2 of 2



| Special Features: |
|------------------------------------|
| Ruggedized |
| Material: |
| Steel |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A310a0