NSN 6625-00-668-9236

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-668-9236

Circuit Current For Which Designed:
Ac
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.650 inches
Mounting Hole Diameter:
Between 0.120 inches and 0.130 inches
Scale Division Quantity:
100 single indicator single range
Frequency Rating:
60.0 hertz
Mounting Stud Length:
0.500 inches
Overall Diameter:
2.695 inches
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 7; lockwasher 5; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
2.250 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Movement Type:
Moving iron vane
Background Color:

White single indicator single range

NSN 6625-00-668-9236

Ammeter - Page 2 of 2

Fiig:



Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
3 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+500.0 milliamperes, ac single indicator single range
Mounting Stud Diameter:
0.112 inches
Scale Selection Method:
Terminal
Features Provided:
Luminous scale marking and magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Phase:
Single
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Test Data Document:
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-10304/7 government specification
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
TWO STATES OF THE STATES OF TH