

View Online at <https://aerobasegroup.com/nsn/6625-00-668-9404>

Circuit Current For Which Designed:

Dc

Overall Length:

1.817 inches

Overall Height:

4.250 inches

Overall Width:

4.000 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

3.000 inches

Environmental Protection:

Dust resistant

Distance Between Mounting Facility Centers:

1.406 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

39.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.630 inches

Meter Body Width Behind Mounting Flange:

3.700 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+1.0 milliamperes, dc single indicator single range

Mounting Stud Diameter:

0.250 inches

Meter Body Height Behind Mounting Flange:

3.950 inches

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

FiiG:

A310a0