

View Online at <https://aerobasegroup.com/nsn/6625-00-668-9404>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.817 inches

**Overall Height:**

4.250 inches

**Overall Width:**

4.000 inches

**Scale Division Quantity:**

50 single indicator single range

**Mounting Stud Length:**

3.000 inches

**Environmental Protection:**

Dust resistant

**Distance Between Mounting Facility Centers:**

1.406 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Sensitivity Rating:**

39.0 millivolts

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.630 inches

**Meter Body Width Behind Mounting Flange:**

3.700 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0/+1.0 milliamperes, dc single indicator single range

**Mounting Stud Diameter:**

0.250 inches

**Meter Body Height Behind Mounting Flange:**

3.950 inches

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**FiiG:**

A310a0