

View Online at <https://aerobasegroup.com/nsn/6625-00-668-9460>

Overall Length:

15.250 inches

Overall Height:

15.000 inches

Overall Width:

17.375 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 440.0 hertz

Accessory Components And Quantity:

11 adapters, 1 power cable, 2 rf cable assembly, 2 probe assembly

Voltage Rating:

Between 100.0 volts and 130.0 volts

Beam Quantity:

1

Screen Size:

3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Trigger Sweep Voltage Amplitude Rating:

Between 25.0 volts and 50.0 volts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

0.2, 1.0, 10, 100, and 500 usec

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

0.05 volts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

3.5 volts any acceptable outside diameter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

110.0 volts any acceptable outside diameter

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

150.0 volts rms per inch

Frequency Response Rating:

Provided

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

5.6 megohms

Y-axis Input Impedance Rating:

0.3 megohms

Z-axis Input Impedance Rating:

0.056 megohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Special Features:

Sweep frequency range: 8 to 800000 cps; x-axis frequency response rating: 8 cycles per sec to 800 kc; y-axis frequency response rating: 2 cycles per sec to 8 mc per sec; z-axis frequency response rating: 6 cycles per sec to 5 mc per sec

Specification Or Standard:

An/usm-25 type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g