

View Online at <https://aerobasegroup.com/nsn/6625-00-669-0100>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

6.112 inches

Overall Height:

6.000 inches

Overall Width:

5.750 inches

Scale Division Quantity:

100 single indicator all ranges

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Term. Hdw 4; lamp 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

100.0 millivolts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-0.5 to 0.5 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0 to 500.0 amperes single indicator 3rd range

Scale Selection Method:

Terminal

Features Provided:

Knife edge pointer and mirror scale and self-illumination facility and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 threaded stud

Operating Voltage Rating In Volts:

6.3 ac

Special Markings:

Two columns: amp; 0-1; 0-2; 0-5; 0-10; 0-20; 0-50; 0-100; millivolts; 0-100; second column: ea division; 10 ma; 20 ma; 50 ma; 100 ma; 200 ma; 500 ma; 1 amp; 5 amp division; 1 mv

Material:

Aluminum or plastic or steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Meets mil-m-16034 requirements

Style Designator:

Rectangular surface mtg

Supplementary Features:

Calibrated for 80.0 in. Leads

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0