NSN 6625-00-669-0748

Voltmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-669-0748

Circuit Current For Which Designed:
Dc
Overall Diameter:
2.695 inches
Mounting Bolt Circle Diameter:
2.440 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
100.0 ohms per volt
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.405 inches
Meter Body Diameter Behind Mounting Flange:
2.210 inches
Background Color:
Background Color: White single indicator single range
_
White single indicator single range
White single indicator single range Mounting Facility Type And Quantity:
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range:
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter:
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches Features Provided:
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches Features Provided: Magnetic shield
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches Features Provided: Magnetic shield Circuit Attachment Method And Quantity:
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Shelf Life:
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Shelf Life: N/a
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Shelf Life: N/a
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Shelf Life: N/a Unit Of Measure:
White single indicator single range Mounting Facility Type And Quantity: 4 threaded stud Measurement Range: +0.0/+50.0 volts, dc single indicator single range Mounting Stud Diameter: 0.112 inches Features Provided: Magnetic shield Circuit Attachment Method And Quantity: 2 solderless lug Shelf Life: N/a Unit Of Measure: Demilitarization: