NSN 6625-00-669-4033

Modulation Meter - Page 1 of 2

Circuit Current For Which Designed:

Dc

Overall Length: 1.938 inches

0.158 inches

Mounting Hole Diameter:

Scale Division Quantity:

100 single indicator single range



View Online at https://aerobasegroup.com/nsn/6625-00-669-4033

+0.0 to 100.0 percent deviation single indicator single range

Overall Diameter:
3.500 inches
Mounting Bolt Circle Diameter:
3.160 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
48.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-20.0 to 20.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.125 inches
Meter Body Diameter Behind Mounting Flange:
2.688 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:

NSN 6625-00-669-4033Modulation Meter - Page 2 of 2



Features Provided:
Magnetic shield and zero adjuster
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Hermetically sealed.Panel for which designed is nonmagnetic. Circuit construction type is non electronic.
Special Markings:
Sealed do not @open
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Cadmium and chromate
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0