

View Online at <https://aerobasegroup.com/nsn/6625-00-670-7624>

Circuit Current For Which Designed:

Dc

Overall Length:

2.304 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.898 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.898 inches

Overall Height:

2.387 inches

Overall Width:

2.387 inches

Mounting Stud Length:

0.565 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 2; washer 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

25.0 microamperes

Dial Scale Marking Color:

Black single indicator single range and red single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.363 inches

Meter Body Diameter Behind Mounting Flange:

2.151 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Red band r side of scale

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Mounting Stud Diameter:

0.109 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0