

View Online at <https://aerobasegroup.com/nsn/6625-00-678-1696>

Overall Length:

19.500 inches

Overall Height:

12.000 inches

Overall Width:

8.500 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 800.0 hertz

Accessory Components And Quantity:

1 green filter, 1 attenuator, 2 adapters, 1 instruction manual

Voltage Rating:

105.0 volts and 250.0 volts

Beam Quantity:

1

Screen Size:

3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+0.017/+2500000.000 hertz

Single Trigger Sweep Duration:

Between 0.000002 seconds and 60.000000 seconds

Trigger Sweep Voltage Amplitude Rating:

50.0 volts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

Ten 1/4 in. Line

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

0.014 volts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

5.6 volts any acceptable major

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 0.0 kilohertz and 500.0 kilohertz

Y-axis Frequency Response Rating:

Between 0.0 megahertz and 10.0 megahertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Z-axis Input Impedance Rating:

1.0 megohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Special Features:

9 kv accelerating potential

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-g