NSN 6625-00-678-1696

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-678-1696

Overall Length:
19.500 inches
Overall Height:
12.000 inches
Overall Width:
8.500 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 800.0 hertz
Accessory Components And Quantity:
1 green filter, 1 attenuator, 2 adapters, 1 instruction manual
Voltage Rating:
105.0 volts and 250.0 volts
Beam Quantity:
1
Screen Size:
3 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Circuit Type:
Horizontal and vertical
Sweep Frequency Range:
+0.017/+2500000.000 hertz
Single Trigger Sweep Duration:
Between 0.000002 seconds and 60.000000 seconds
Trigger Sweep Voltage Amplitude Rating:
50.0 volts
Trigger Sweep Polarity Switch:
Included
Trigger Sweep Marker Intervals:
Ten 1/4 in. Line
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
0.014 volts rms per inch
Horizontal Deflection Sensitivity Voltage Rating:
5.6 volts any acceptable major

NSN 6625-00-678-1696

Oscilloscope - Page 2 of 2



Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Provided
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
Between 0.0 kilohertz and 500.0 kilohertz
Y-axis Frequency Response Rating:
Between 0.0 megahertz and 10.0 megahertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Z-axis Input Impedance Rating:
1.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Special Features:
9 kv accelerating potential
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
T320-g