

View Online at <https://aerobasegroup.com/nsn/6625-00-679-6681>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

Between 2.020 inches and 2.040 inches

**Scale Division Quantity:**

4 single indicator single range

**Mounting Stud Length:**

0.980 inches

**Overall Diameter:**

Between 2.280 inches and 2.330 inches

**Environmental Protection:**

Water resistant

**Distance Between Mounting Facility Centers:**

0.875 inches

**Furnished Items And Quantity:**

Term. Hdw 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Two hole/stud

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

Between 0.820 inches and 0.840 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 2.070 inches and 2.090 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator single range

**Pointer Color:**

White single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 clamp and 2 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

-40.0/+40.0 amperes single indicator single range

**Mounting Stud Diameter:**

Between 0.187 inches and 0.190 inches

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Term. And mtg studs are the same

**Special Markings:**

Plus sign on right front of meter face below scale and minus sign on left front of meter face below scale

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Supplementary Features:**

Bezel color: bright chrome

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0