

View Online at <https://aerobasegroup.com/nsn/6625-00-679-7694>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

4.870 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.470 inches and 2.478 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 2.470 inches and 2.478 inches

Overall Height:

3.260 inches

Overall Width:

3.260 inches

Mounting Hole Diameter:

0.170 inches

Scale Division Quantity:

20 all indicators all ranges

Environmental Protection:

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

White all indicators all ranges

Accuracy In Percent:

-2.5/+2.5 at full scale all indicators all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

3.985 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black all indicators all ranges

Pointer Color:

White all indicators all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear all indicators all ranges

Measurement Range:

+0.0/+20.0 amperes 2nd indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

Luminous scale marking and magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 solder lug

Special Features:

Ruggedized

Special Markings:

Term. Marked: + aadcp a; - aadcp b; local + c; local - d

Material:

Stainless steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel semigloss

Special Test Features:

Conforms to mil-m-10304, type mr36b200dcua

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0