

View Online at <https://aerobasegroup.com/nsn/6625-00-679-7694>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

500.0

**Overall Length:**

4.870 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 2.470 inches and 2.478 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 2.470 inches and 2.478 inches

**Overall Height:**

3.260 inches

**Overall Width:**

3.260 inches

**Mounting Hole Diameter:**

0.170 inches

**Scale Division Quantity:**

20 all indicators all ranges

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

200.0 microamperes

**Dial Scale Marking Color:**

White all indicators all ranges

**Accuracy In Percent:**

-2.5/+2.5 at full scale all indicators all ranges

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

3.985 inches

**Meter Body Diameter Behind Mounting Flange:**

2.800 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black all indicators all ranges

**Pointer Color:**

White all indicators all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Linear all indicators all ranges

**Measurement Range:**

+0.0/+20.0 amperes 2nd indicator 2nd range

**Scale Selection Method:**

Terminal

**Features Provided:**

Luminous scale marking and magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

Term. Marked: + aadcp a; - aadcp b; local + c; local - d

**Material:**

Stainless steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel semigloss

**Special Test Features:**

Conforms to mil-m-10304, type mr36b200dcua

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0