NSN 6625-00-679-7694

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-679-7694

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
500.0
Overall Length:
4.870 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 2.470 inches and 2.478 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 2.470 inches and 2.478 inches
Overall Height:
3.260 inches
Overall Width:
3.260 inches
Mounting Hole Diameter:
0.170 inches
Scale Division Quantity:
20 all indicators all ranges
Environmental Protection:
Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
200.0 microamperes
Dial Scale Marking Color:
White all indicators all ranges
Accuracy In Percent:
-2.5/+2.5 at full scale all indicators all ranges
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
3.985 inches
Meter Body Diameter Behind Mounting Flange:
2.800 inches
Movement Type:
Moving coil, permanent magnet

Background Color:
Black all indicators all ranges

NSN 6625-00-679-7694

Ammeter - Page 2 of 2



Pointer Color:
White all indicators all ranges
Power Source:
External
Mounting Facility Type And Quantity:
4 unthreaded hole
Scale Graduation Type:
Linear all indicators all ranges
Measurement Range:
+0.0/+20.0 amperes 2nd indicator 2nd range
Scale Selection Method:
Terminal
Features Provided:
Luminous scale marking and magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
4 solder lug
Special Features:
Ruggedized
Special Markings:
Term. Marked: + aadcp a; - aadcp b; local + c; local - d
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to mil-m-10304, type mr36b200dcua
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0