

View Online at <https://aerobasegroup.com/nsn/6625-00-679-9335>

Circuit Current For Which Designed:

Dc

Overall Length:

2.496 inches

Overall Height:

0.515 inches

Overall Width:

1.600 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

16 single indicator single range

Distance Between Mounting Facility Centers:

1.285 inches

Barrel Width:

1.600 inches

Furnished Items And Quantity:

Mtg hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0/+3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.010 inches

Meter Body Width Behind Mounting Flange:

1.600 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 bracket and 2 screw and 2 threaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+800.0 milliamperes, dc single indicator single range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

0.965 inches

Meter Barrel Depth:

1.622 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

40 ohms resistance

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Supplementary Features:

2.0 seconds maximum response time

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0