

View Online at <https://aerobasegroup.com/nsn/6625-00-682-2581>

Overall Length:

23.000 inches

Overall Height:

15.750 inches

Overall Width:

19.750 inches

Environmental Protection:

General purpose

Vibration Resistance Range In Hertz:

Not rated

Shock Resistance Rating In Gravitational Units:

Not rated

Operating Temperature Range:

-40.0 to 55.0 degrees celsius

Average Life Measurement:

Hours

Basic Shape Style:

Rectangular or square

Identification Designator:

An/upm-15a-80058

Maximum Operating Altitude Rating:

6000.0 feet

Inclosure Type:

Encased

Operating Control Method:

Manual

Installation Design:

Portable

Control Type:

Local

Circuit Construction Type:

Electron tube

Frequency Per Channel:

50.0 hertz operating channel

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

Not rated

Overall Gain:

Not rated

Impedance Rating Per Channel:

50.000 ohms output channel

Pulse Duration Per Channel:

100.000 microseconds output channel

Pulse Rise Time Per Channel:

50.000 nanoseconds operating channel

Pulse Decay Time Per Channel:

400.000 nanoseconds output channel

Polarity Per Channel:

Positive output channel

Pulse Repetition Rate Per Channel:

50.000 pulses per second operating channel

Pulse Peak Amplitude Per Channel:

200.000 volts output channel

Signal Data Type Per Channel:

Output channel pulse

Calibrated Tolerance In Percent:

-5.0 to 5.0

Output Wave Shape:

Rectangular

Indicator Device Type And Quantity:

1 light

Maximum Continuous Operating Time In Hours:

Not rated

Connection Type And Location:

Receptacle, power front and receptacle, coaxial front

Operating Ac Frequency In Hertz:

50.0 single voltage

Calibration Function:

Pulse repetition

Connection Contact Type And Quantity:

3 receptacle, coaxial internal and 1 receptacle, power external

External Ac Operating Voltage In Volts:

115.0 single voltage

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A32200