NSN 6625-00-684-1088

Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-684-1088

| Dielectric Withstanding Voltage In Volts: |
|---------------------------------------------------------|
| 1500.0 |
| Overall Length: |
| 2.906 inches |
| Mounting Hole Diameter: |
| 0.156 inches |
| Scale Division Quantity: |
| 7 single indicator single range |
| Overall Diameter: |
| 3.500 inches |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Installation Design: |
| Panel |
| Register Quantity: |
| 1 |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Frequency Response Range: |
| +380.000 to 420.000 hertz |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Resonant Reed Quantity: |
| 9 |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.450 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.580 inches |
| Movement Type: |
| Vibrating reed |
| Background Color: |
| White single indicator single range |
| Power Source: |
| External |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |

+380.0 to 420.0 hertz single indicator single range

NSN 6625-00-684-1088

Electrical Frequency Meter - Page 2 of 2



| Circuit Attachment Method And Quantity: |
|----------------------------------------------|
| 2 solder lug |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Surface Treatment: |
| Enamel |
| Style Designator: |
| Round flush mtg |
| Supplementary Features: |
| nsulation resistance 100 mego min at 500 vdc |
| Fsc Application Data: |
| Test set, electronic equipment |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| . - |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |