

View Online at <https://aerobasegroup.com/nsn/6625-00-684-1271>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.380 inches

Mounting Hole Diameter:

0.150 inches

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Lock washers 3; hex nuts 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

10.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

In-out 0-1500 knots range rate

Mounting Facility Type And Quantity:

1 flange and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 solderless lug

Special Features:

Nonlinear scale

Special Markings:

Caption knots range rate located lower center of dial; div scale divided into 7 segments varied size marked w 1/8 in. Black circles w white numerals

Material:

Plastic and steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0