

View Online at <https://aerobasegroup.com/nsn/6625-00-684-3350>

Circuit Current For Which Designed:

Dc

Overall Length:

Between 2.340 inches and 2.480 inches

Scale Division Quantity:

4 single indicator single range

Mounting Stud Length:

0.500 inches

Overall Diameter:

Between 2.280 inches and 2.320 inches

Distance Between Mounting Facility Centers:

1.320 inches

Furnished Items And Quantity:

Terminal hardware 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 1.500 inches and 1.540 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.030 inches and 2.090 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

White single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp and 2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-40.0/+40.0 amperes single indicator single range

Mounting Stud Diameter:

0.190 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Bezel sealed with rubber gasket

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Supplementary Features:

Bezel is satin finish and stainless steel; .620 inch diameter dust hole closed with plastic plug

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiiig:

A310a0