

View Online at <https://aerobasegroup.com/nsn/6625-00-684-5764>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.911 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.020 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.570 inches

**Overall Height:**

4.250 inches

**Overall Width:**

4.680 inches

**Scale Division Quantity:**

100 single indicator single range

**Mounting Stud Length:**

0.312 inches

**Environmental Protection:**

Airtight and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and watertight

**Furnished Items And Quantity:**

Nut 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

2.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.880 inches

**Meter Body Diameter Behind Mounting Flange:**

2.740 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 10.0 ohms single indicator single range

**Mounting Stud Diameter:**

0.138 inches

**Scale Selection Method:**

Terminal

**Features Provided:**

Mirror scale and zero adjuster

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0