

View Online at <https://aerobasegroup.com/nsn/6625-00-684-5764>

Circuit Current For Which Designed:

Dc

Overall Length:

1.911 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.020 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.570 inches

Overall Height:

4.250 inches

Overall Width:

4.680 inches

Scale Division Quantity:

100 single indicator single range

Mounting Stud Length:

0.312 inches

Environmental Protection:

Airtight and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and watertight

Furnished Items And Quantity:

Nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

2.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.880 inches

Meter Body Diameter Behind Mounting Flange:

2.740 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 10.0 ohms single indicator single range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Mirror scale and zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0