NSN 6625-00-691-5223

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-691-5223
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
2.562 inches
Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
50 single indicator single range
Overall Diameter:
3.510 inches
Environmental Protection:
Shock resistant and vibration resistant and watertight
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Mtg hdw 3; term. Hdw 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
50.0 amperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.281 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

NSN 6625-00-691-5223

Ammeter - Page 2 of 2



Power Source:
External
Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0/+50.0 amperes, dc single indicator single range
Features Provided:
External shunting and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to mil-m-10304, type mr36w50dcaar
Style Designator:
Round flush mtg
Supplementary Features:
50 millivolt full scale external shunt
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0