

View Online at <https://aerobasegroup.com/nsn/6625-00-702-5663>

Circuit Current For Which Designed:

Dc

Overall Length:

2.130 inches

Scale Division Quantity:

40 single indicator all ranges

Mounting Stud Length:

0.630 inches

Overall Diameter:

2.695 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Gasket 1; nut 7; washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

5.0 milliamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.520 inches

Meter Body Diameter Behind Mounting Flange:

2.200 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+40.0 milliamperes, dc single indicator 1st range

Mounting Stud Diameter:

0.112 inches

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and zero adjuster

Circuit Attachment Method And Quantity:

2 solderless lug

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Special Test Features:

Conforms to mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0