

View Online at <https://aerobasegroup.com/nsn/6625-00-702-7276>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Not established

Overall Length:

2.850 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

Between 2.984 inches and 3.130 inches

Overall Width:

Between 2.984 inches and 3.130 inches

Scale Division Quantity:

10 single indicator single range

Mounting Stud Length:

0.375 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

50.0 millivolts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.010 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.734 inches and 2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-50.0/+50.0 microamperes, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Black line at - 50 ua, marked with -; red line at -25 ua with red shaded area from -22.5 to -27.5 and -2.5 to 2.5 ua; red line at 0; red line at 25 ua with red shaded area from 22.5 to 27.5 ua; black line at 50 ua marked +

Material:

Glass and plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0