NSN 6625-00-702-8867

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-702-8867

Overall Length:
26.813 inches
Overall Height:
14.375 inches
Overall Width:
13.500 inches
Current Type:
Ac
Frequency Rating:
60.0 hertz
Accessory Components And Quantity:
1 shield, light, 1 assembly, mirror, 2 lead, test
Voltage Rating:
120.0 volts
Beam Quantity:
1
Mounting Method:
Rack
Screen Size:
5 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Frequency Range:
+20.000/+500000.000 hertz
Single Trigger Sweep Duration:
0.5 microseconds
Trigger Sweep Voltage Amplitude Rating:
0.5 volts
Trigger Sweep Polarity Switch:
Not included
Trigger Sweep Marker Intervals:
1.0 usec and 10.0
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
100.0 millivolts rms per inch
Horizontal Deflection Sensitivity Voltage Rating:

5.0 volts any acceptable outside diameter

NSN 6625-00-702-8867

Oscilloscope - Page 2 of 2



Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Not provided
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
Between 20.0 hertz and 500000.0 hertz
Y-axis Frequency Response Rating:
Between 5.0 hertz and 3000000.0 hertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
100.0 kilohms
Y-axis Input Impedance Rating:
1.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T320-g