

View Online at <https://aerobasegroup.com/nsn/6625-00-708-7900>

Circuit Current For Which Designed:

Dc

Overall Length:

2.685 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

200 single indicator single range

Overall Diameter:

4.500 inches

Environmental Protection:

Cold resistant and heat resistant and humidity resistant and shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

4.125 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Six hole/stud bolt circle

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.090 inches

Meter Body Diameter Behind Mounting Flange:

3.562 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

6 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+200.0 microamperes, dc single indicator single range

Features Provided:

Knife edge pointer and zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 solder lug

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0