

View Online at <https://aerobasegroup.com/nsn/6625-00-708-9908>

Circuit Current For Which Designed:

Dc

Overall Length:

2.003 inches

Scale Division Quantity:

30 single indicator single range

Overall Diameter:

2.125 inches

Environmental Protection:

Dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant

Furnished Items And Quantity:

Nut 2; lockwasher 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.732 inches

Meter Body Diameter Behind Mounting Flange:

2.008 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

1 clamp

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-30.0/+30.0 amperes, dc single indicator single range

Scale Selection Method:

Terminal

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Mark + on right side by the 30; mark - on left side by 30

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0