

View Online at <https://aerobasegroup.com/nsn/6625-00-708-9908>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.003 inches

**Scale Division Quantity:**

30 single indicator single range

**Overall Diameter:**

2.125 inches

**Environmental Protection:**

Dust resistant and fungus resistant and humidity resistant and shock resistant and vibration resistant

**Furnished Items And Quantity:**

Nut 2; lockwasher 2

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0/+2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.732 inches

**Meter Body Diameter Behind Mounting Flange:**

2.008 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 clamp

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

-30.0/+30.0 amperes, dc single indicator single range

**Scale Selection Method:**

Terminal

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Markings:**

Mark + on right side by the 30; mark - on left side by 30

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Paint

**Special Test Features:**

Complies with mil-m-10304

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0