

View Online at <https://aerobasegroup.com/nsn/6625-00-713-9068>

**Width:**

15.000 inches

**Length:**

20.500 inches

**Ac Voltage Rating:**

115.0 volts

**Frequency Rating:**

Between 50.0 hertz and 400.0 hertz

**Major Components:**

Test set; cable assembly, rf; cable assembly, special purpose, elect

**Accessory Component Quantity:**

1 and 13 and 1

**Accessory Controlling Agency:**

Bell aircraft corp

**Accessory Identifying Number:**

60905-009-1 part no. And 60901-004-17 part no. And 60901-007-1 part no.

**Internal Battery Accommodation:**

Not included

**Material And Location:**

Aluminum carrying case

**Inclosure Feature:**

Multiple item w/carrying case

**Test Type For Which Designed:**

Measurement of pulse position width and amplitude; measurement of transistor data and collector-base current

**Operating Test Capability:**

Kpulse generator, pulse trains /group/ 2 to 15 pulses, pulse train repetition rate 150 to 425 per sec, amplitude 0 to 9 v pk pulse w 0.2 to 1.0 usec; trigger pulse generator, amplitude 15.0 v pk min, pulse w 1.0 usec repetition rate 150 to 425 pulses per sec, output impedance 50 ohm amplitude 15.0 vpk min pulse w 1.0 usec, repetition rate 37 to 106 pulses per sec, output impedance 50 ohm amplitude 10 v pk nom pulse w 1.0 usec, repetition rate 150 to 425 pulses per sec, output impedance 500 ohm; pulse measurement, 2 pulse trains, amplitude sensitivi type 30 v pk min pulse w 0.9 porm 0.1 usec, repetition rate 150 to 425 pulses per sec position porm 0.0 usec; transistor measurement, beta gain 20 to 25, collector-base current 1 to 75 ua

**Phase:**

Single

**Height:**

14.000 inches

**Specification Or Standard:**

An/gpm-40 type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

T228-a