

View Online at <https://aerobasegroup.com/nsn/6625-00-714-3992>

Overall Length:

24.000 inches

Overall Height:

16.750 inches

Overall Width:

13.000 inches

Current Type:

Ac

Frequency Rating:

60.0 hertz

Accessory Components And Quantity:

Adapter, binding post 2, cord, power 1, filter, light 1, lead, test 1, manual, instruction 1, probe, 10-x attenuation 2

Voltage Rating:

115.0 volts

Beam Quantity:

1

Screen Size:

5 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Frequency Range:

+0.0/+100.0 kilohertz

Trigger Sweep Voltage Amplitude Rating:

100.0 volts

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

50.0 volts peak to peak per centimeter

Horizontal Deflection Sensitivity Voltage Rating:

200.0 millivolts any acceptable megahertz

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

7.0 volts any acceptable megahertz

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

30.0 volts peak to peak per centimeter

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

1.0 hertz and 240.0 hertz

Y-axis Frequency Response Rating:

5.0 hertz and 30000000.0 hertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Z-axis Input Impedance Rating:

1.0 megohms

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Special Features:

For dual trace application, type c-a dc to 24 mc, 15 nano second risetime at 0.05 v/cm to 50.00 v/cm

Fsc Application Data:

Oscilloscope, except specially designed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T320-g