

View Online at <https://aerobasegroup.com/nsn/6625-00-717-3571>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

4.075 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.744 inches and 0.756 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 3.799 inches and 3.811 inches

Overall Height:

1.437 inches

Overall Width:

4.171 inches

Mounting Hole Diameter:

0.138 inches

Scale Division Quantity:

50 single indicator single range

Environmental Protection:

Cold resistant and shock resistant and vibration resistant and watertight

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.594 inches

Meter Body Width Behind Mounting Flange:

3.421 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0; 100

Mounting Facility Type And Quantity:

4 threaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

1.328 inches

Features Provided:

Self-illumination facility

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 solderless lug

Material:

Aluminum

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0