

View Online at <https://aerobasegroup.com/nsn/6625-00-717-3571>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

4.075 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 0.744 inches and 0.756 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 3.799 inches and 3.811 inches

**Overall Height:**

1.437 inches

**Overall Width:**

4.171 inches

**Mounting Hole Diameter:**

0.138 inches

**Scale Division Quantity:**

50 single indicator single range

**Environmental Protection:**

Cold resistant and shock resistant and vibration resistant and watertight

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.594 inches

**Meter Body Width Behind Mounting Flange:**

3.421 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

0; 100

**Mounting Facility Type And Quantity:**

4 threaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Meter Body Height Behind Mounting Flange:**

1.328 inches

**Features Provided:**

Self-illumination facility

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 solderless lug

**Material:**

Aluminum

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0