## NSN 6625-00-720-3030

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-720-3030

Circuit Current For Which Designed:
Ac
Overall Length:
1.910 inches
Mounting Hole Diameter:
0.150 inches
Overall Diameter:
3.510 inches
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Mounting screws 3 lockwashers 3 nuts 3
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
2000.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
•
-2.0/+2.0 at full scale single indicator single range
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.660 inches
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.660 inches  Meter Body Diameter Behind Mounting Flange:
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.660 inches  Meter Body Diameter Behind Mounting Flange:  2.820 inches
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.660 inches  Meter Body Diameter Behind Mounting Flange:  2.820 inches  Movement Type:
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.660 inches  Meter Body Diameter Behind Mounting Flange:  2.820 inches  Movement Type:  Moving iron vane
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.660 inches  Meter Body Diameter Behind Mounting Flange: 2.820 inches  Movement Type:  Moving iron vane  Background Color:
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.660 inches  Meter Body Diameter Behind Mounting Flange: 2.820 inches  Movement Type:  Moving iron vane  Background Color:  White single indicator single range
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.660 inches  Meter Body Diameter Behind Mounting Flange: 2.820 inches  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Mounting Facility Type And Quantity:
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.660 inches  Meter Body Diameter Behind Mounting Flange: 2.820 inches  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Mounting Facility Type And Quantity: 3 unthreaded hole
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  1.660 inches  Meter Body Diameter Behind Mounting Flange:  2.820 inches  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range:
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.660 inches  Meter Body Diameter Behind Mounting Flange: 2.820 inches  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+1.0 amperes, ac single indicator single range
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.660 inches  Meter Body Diameter Behind Mounting Flange: 2.820 inches  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+1.0 amperes, ac single indicator single range  Movement Suspension Method:
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.660 inches  Meter Body Diameter Behind Mounting Flange: 2.820 inches  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+1.0 amperes, ac single indicator single range  Movement Suspension Method:  Jewel pivot base
-2.0/+2.0 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 1.660 inches  Meter Body Diameter Behind Mounting Flange: 2.820 inches  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+1.0 amperes, ac single indicator single range  Movement Suspension Method:  Jewel pivot base  Circuit Attachment Method And Quantity:

**Style Designator:** Round flush mtg

## NSN 6625-00-720-3030

Ammeter - Page 2 of 2



_					
٠.	n	_	I+	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0