NSN 6625-00-720-3184

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-720-3184

D-
Dc
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
30 single indicator single range
Overall Diameter:
2.695 inches
Mounting Bolt Circle Diameter:
2.440 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
50.0 millivolts
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.860 inches
Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange: 2.210 inches
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type:
Meter Body Diameter Behind Mounting Flange: 2.210 inches
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type:
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color:
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity:
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range:
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+3.0 amperes, dc single indicator single range
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+3.0 amperes, dc single indicator single range Features Provided:
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+3.0 amperes, dc single indicator single range Features Provided: Magnetic shield
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+3.0 amperes, dc single indicator single range Features Provided: Magnetic shield Movement Suspension Method:
Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+3.0 amperes, dc single indicator single range Features Provided: Magnetic shield Movement Suspension Method: Jewel pivot base

Nonhardened

Nuclear Hardness Critical Feature:

Plastic

NSN 6625-00-720-3184

Ammeter - Page 2 of 2



•		
StVID	l Jacian	ator.
OLYIC	Design	atoi.

Round flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0