

View Online at <https://aerobasegroup.com/nsn/6625-00-723-4620>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.650 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Overall Diameter:**

2.695 inches

**Mounting Bolt Circle Diameter:**

2.440 inches

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Three hole/stud bolt circle

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.5 to 2.5 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

2.250 inches

**Meter Body Diameter Behind Mounting Flange:**

2.210 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

3 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0 to 80.0 volts, dc single indicator single range

**Circuit Attachment Method And Quantity:**

2 threaded stud and 2 solder lug

**Operating Voltage Rating In Volts:**

115.0 dc

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Test Data Document:**

81349-mil-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A310a0