

View Online at <https://aerobasegroup.com/nsn/6625-00-723-4620>

Circuit Current For Which Designed:

Dc

Overall Length:

2.650 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.5 to 2.5 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.250 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+0.0 to 80.0 volts, dc single indicator single range

Circuit Attachment Method And Quantity:

2 threaded stud and 2 solder lug

Operating Voltage Rating In Volts:

115.0 dc

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Test Data Document:

81349-mil-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0