

View Online at <https://aerobasegroup.com/nsn/6625-00-725-1558>

Overall Length:

14.000 inches

Overall Height:

12.750 inches

Overall Width:

6.875 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Accessory Components And Quantity:

Adapters 3, box, viewing 1, cable assembly 6, misc hardware and tools

Voltage Rating:

115.0 volts

Beam Quantity:

1

Screen Size:

1-1/2 in. By 3 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+200.000/+200000.000 hertz

Single Trigger Sweep Duration:

0.2 microseconds

Trigger Sweep Voltage Amplitude Rating:

Between 2.0 volts and 15.0 volts

Trigger Sweep Polarity Switch:

Not included

Trigger Sweep Marker Intervals:

1000 u sec

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

10.0 millivolts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

1.0 volts any acceptable outside diameter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Provided

X-axis Frequency Response Rating:

Between 60.0 hertz and 1500000.0 hertz

Y-axis Frequency Response Rating:

Between 20.0 hertz and 500000.0 hertz

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

390.0 kilohms

Y-axis Input Impedance Rating:

1.0 megohms

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g