NSN 6625-00-725-1558

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-725-1558

Overall Length:
14.000 inches
Overall Height:
12.750 inches
Overall Width:
6.875 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 400.0 hertz
Accessory Components And Quantity:
Adapters 3, box, viewing 1, cable assembly 6, misc hardware and tools
Voltage Rating:
115.0 volts
Beam Quantity:
1
Screen Size:
1-1/2 in. By 3 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Circuit Type:
Horizontal and vertical
Sweep Frequency Range:
+200.000/+200000.000 hertz
Single Trigger Sweep Duration:
0.2 microseconds
Trigger Sweep Voltage Amplitude Rating:
Between 2.0 volts and 15.0 volts
Trigger Sweep Polarity Switch:
Not included
Trigger Sweep Marker Intervals:
1000 u sec
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
10.0 millivolts rms per inch
Horizontal Deflection Sensitivity Voltage Rating:

1.0 volts any acceptable outside diameter

NSN 6625-00-725-1558

Oscilloscope - Page 2 of 2



Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Not provided
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:
Between 60.0 hertz and 1500000.0 hertz
Y-axis Frequency Response Rating:
Between 20.0 hertz and 500000.0 hertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
390.0 kilohms
Y-axis Input Impedance Rating:
1.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T320-g