

View Online at <https://aerobasegroup.com/nsn/6625-00-728-6028>

Circuit Current For Which Designed:

Dc

Overall Length:

1.976 inches

Mounting Hole Diameter:

0.138 inches

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 5; washer 5

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+0.060 to 10.000 kilohertz

Sensitivity Rating:

1.0 milliwatts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.063 inches

Meter Body Diameter Behind Mounting Flange:

2.675 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-20.0 to 2.0 decibels above or below one milliwatt single indicator 1st range

Features Provided:

External shunting and magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Sealed do not open on back of meter; left term. Has p sign

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Chromate

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0