NSN 6625-00-728-6029

Circuit Current For Which Designed:

Standing Wave Ratio Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-728-6029

Dc
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.312 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.312 inches
Overall Height:
1.750 inches
Overall Width:
1.750 inches
Mounting Hole Diameter:
0.136 inches
Environmental Protection:
Dustproof
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.250 inches
Meter Body Diameter Behind Mounting Flange:
1.510 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Mounting Facility Type And Quantity:
4 unthreaded hole
Scale Graduation Type:

Measurement Range:

+1.0 to 3.0 kilowatts single indicator 1st range

Nonlinear single indicator all ranges

NSN 6625-00-728-6029

Standing Wave Ratio Meter - Page 2 of 2



Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Red line at 2.0
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set electronic
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0