NSN 6625-00-729-6723

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-729-6723

| 3 |
|---|
| Circuit Current For Which Designed: |
| Ac |
| Overall Length: |
| 2.810 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Overall Diameter: |
| 3.500 inches |
| Mounting Bolt Circle Diameter: |
| 1.578 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Frequency Response Range: |
| +0.000 to 400.000 hertz |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.410 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.672 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Power Source: |
| External |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0 to 120.0 volts, ac single indicator single range |
| |
| Features Provided: |
| Features Provided: Zero adjuster |

Jewel pivot base

NSN 6625-00-729-6723

Voltmeter - Page 2 of 2



| Circuit Attachment Method And Quantity: |
|---|
| 2 solder lug |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, elect. Equip. |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Yes - demil/mli

Fiig: A310a0