

View Online at <https://aerobasegroup.com/nsn/6625-00-732-1112>

Circuit Current For Which Designed:

Dc

Overall Length:

1.605 inches

Overall Height:

1.743 inches

Overall Width:

1.750 inches

Scale Division Quantity:

30 single indicator single range

Mounting Stud Length:

0.500 inches

Distance Between Mounting Facility Centers:

2.470 inches

Furnished Items And Quantity:

Nut 4; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

2.0 amperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.880 inches

Meter Body Diameter Behind Mounting Flange:

1.503 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+0.3 amperes, dc single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Internal shunting and magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Terminal voltage drop 50 millivolts

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0