

View Online at <https://aerobasegroup.com/nsn/6625-00-732-2358>

Circuit Current For Which Designed:

Ac and dc

Dielectric Withstanding Voltage In Volts:

3000.0

Furnished Items And Quantity:

Mounting hardware 3

Indicator Type:

Dial w/pointer

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0/+40.0 volts, dc single indicator 4th range

Features Provided:

Zero adjuster

Meter Replacement Type:

Multimeter

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize

Test Data Document:

81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-m-10304/4 government specification

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0