## NSN 6625-00-732-2358

Replacement Meter - Page 1 of 2

**Fsc Application Data:** 

Test set, electronic equipment



View Online at https://aerobasegroup.com/nsn/6625-00-732-2358

Circuit Current For Which Designed:
Ac and dc
Dielectric Withstanding Voltage In Volts:
3000.0
Furnished Items And Quantity:
Mounting hardware 3
Indicator Type:
Dial w/pointer
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Scale Graduation Type:
Nonlinear single indicator all ranges
Measurement Range:
+0.0/+40.0 volts, dc single indicator 4th range
Features Provided:
Zero adjuster
Meter Replacement Type:
Multimeter
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Anodize
Test Data Document:
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-10304/4 government specification

## NSN 6625-00-732-2358

Replacement Meter - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0