

View Online at <https://aerobasegroup.com/nsn/6625-00-738-2087>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2800.0

**Overall Length:**

4.467 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

6.125 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.325 inches

**Overall Height:**

6.880 inches

**Overall Width:**

6.630 inches

**Scale Division Quantity:**

50 single indicator single range

**Mounting Stud Length:**

0.760 inches

**Environmental Protection:**

Dustproof

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+25.000 to 125.000 hertz

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.0 to 1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.850 inches

**Meter Body Width Behind Mounting Flange:**

5.750 inches

**Movement Type:**

Moving iron vane

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 500.0 volts, ac single indicator single range

**Mounting Stud Diameter:**

0.138 inches

**Scale Selection Method:**

Terminal

**Meter Body Height Behind Mounting Flange:**

6.000 inches

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

4 threaded stud

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel lusterless

**Style Designator:**

Rectangular semi-flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0