

View Online at <https://aerobasegroup.com/nsn/6625-00-740-0344>

Width:

13.200 inches

Length:

19.200 inches

Ac Voltage Rating:

Between 115.0 volts and 230.0 volts

Dc Voltage Rating:

28.0 volts

Frequency Rating:

Between 50.0 hertz and 400.0 hertz

Major Components:

Generator; voltmeter, electronic; attenuator, impedance matching; cable assembly, power electrical; cable assembly, radio frequency

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jetds and jetds and jetds and jetds and jetds

Accessory Identifying Number:

Sg-543a/u type no. And me-260a/u type no. And cn-4071/usm-181 type no. And cx-9031/u type no. And cg-3566/u type no.

Joint Electronics Type Designation System Item Name:

Test set, telephone

Joint Electronics Type Designation System Item Type Number:

Type no. An/usm-181a

Electrical Power Source Relationship:

Operating

Internal Battery Accommodation:

Included

Material And Location:

Aluminum carrying case

Inclosure Feature:

Multiple item w/carrying case

Test Type For Which Designed:

Alignment of multichannel communication systems; measurement of gain, attenuation, and freq response

Operating Test Capability:

Signal generator, range 5 hz to 560 khz, freq response 0.25 db into ratedload dial accuracy prom 3 pct output impedance, 600 ohms output, 10 mw into 600 ohms; electronic voltmeter, range 0.001 to 300 v rms full scale freq range 5hz to 2 mhz; receiver, range 50 hz to 560 khz attenuation 110 db in 1 db step

Phase:

Single

Special Features:

With battery recharging capability

Height:

8.370 inches

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T228-a